

MAXGE

SAFE GREEN SMART



MAXGE

MR-BREAKER



- **MAXGE ELECTRIC**
Deqing Huzhou Zhejiang
- **MAXGE EUROPE, S.A**
Madrid Spain
- **MAXGE ELECTRIC (WUHU)**
Wanzhi Wuhu Anhui
- **MAXGE INTELLIGENT (HANGZHOU)**
Yuhang Hangzhou Zhejiang
- **EMA NEW ENERGY (WENZHOU)**
Yueqing Wenzhou Zhejiang

**NEW ENERGY
CHARGING STATION**

System certification by **SGS**
ISO9001 ISO14001 ISO45001 



■ Committed to becoming a **world-class manufacturer** of intelligent electric

COMPACT AC WALL BOX

Product



IEC62196(Type2)



Model

EVD02

Communication protocol

Private Protocol/OCPP 1.6J

Overall dimensions(mm)

265*215*94mm

Networking methods

Ethernet/4G/WIFI/Bluetooth/APP

Human-computer interaction

LED Display
LED indicator strip

Operation mode

/

AC power supply

230V AC±10%; 50Hz

Executive standard

IEC 61851-1:2017

Rated input and output current

32A

Charging cable length

Standard 5 meters
(Other lengths are also available)

Rated output power

7.4kW

Protection grade

IP65(Control Box)

Working enviroment

Altitude: ≤2000m;
Temperature: -25°C~+45°C

Protection function

Overvoltage protection, undervoltage protection,
overload protection, short circuit protection,
grounding protection,
over temperature protection, communication
abnormality protection,
leakage protection

Charging method

Swipe card

Model

Max Current

Max Power

Rated Voltage

Remark

EVD0207

32A

7.4KW

AC 220-240V

European standard 12 Connector

EVD0222

32A

22KW

AC 380-400V

Remark: Support RFID, APP (Cable, Wifi, 4G), Load Balance, etc.

PORTABLE EV CHARGER

Product



Model	EVE0103		Communication protocol	/
Overall dimensions(mm)	229*119*67mm		Networking methods	/
Human-computer interaction	LED Display LED indicator strip		Operation mode	/
AC power supply	230V AC±10%; 50Hz		Executive standard	IEC 62752: 2016+A1
Rated input and output current	16A		Charging cable length	Standard 5 meters (Other lengths are also available)
Rated output power	3.7kW		Protection grade	IP65(Control Box)
Working enviroment	Altitude: ≤2000m; Temperature: -25°C~+45°C		Protection function	Overvoltage protection, undervoltage protection, overload protection, grounding protection, overcurrent protection, leakage protection, over temperature protection
Charging method				
Model	Max Current	Max Power	Rated Voltage	Remark
EVE0103	16A	3.7KW	230V	European standard



Hacemos realidad un futuro electrificado

Líderes en innovación y producción automatizada

133.000 m²
de fábricas robotizadas



Enfocados en la Industria 4.0 con centros de producción totalmente robotizados, dedicados a la fabricación de equipamiento eléctrico.

+90%
de automatización



Nuestros procesos y sistemas de gestión SAP, líneas de producción y ensamblaje, inspección y control de calidad, están automatizados en más de un 90%.

+60 países
en los 5 continentes



Desde nuestros centros productivos en Asia, con más de 1.000 trabajadores, servimos a más de 60 países en los 5 continentes.

Un fabricante multinacional que lidera la producción de soluciones en:

- **Automatización industrial**
- **Energía solar fotovoltaica**
- **Movilidad eléctrica**
- **Control Smart de instalaciones eléctricas**
- **Eficiencia energética**



Todos los procesos productivos y sistemas de calidad están avalados por los estándares ISO9001, ISO14001 y OHSAS18001.

ISO9001
ISO14001
OHSAS18001

