

GENERAL-PURPOSE RELAY

Features

- Various relays, including LED, test button
- With 4Z contact forms
- With various terminal types
- Gilt contact types
- Transparent dust-proof cover, Various mounting types
- Various sockets available

Contact Ratings

Contact Ratings	4NANC
Contact Resistance	50m (1A 6VDC)
Contact capacity	5A/220VAC
	30VDC125VAC

Specification

Insulation Resistance	500M , 500VDC
Dielectric Strength	BCC 1000VAC 1min
	BOC 1500VAC 1min
	CCC 1500VAC 1min
Operate Time	25ms /25ms
Terminal Type	PCB and Socket

Coil Ratings

Nominal Coil Power	0.9W/1.2VA
--------------------	------------

Coil Versions

Nominal Voltage VDC	Pull-in Voltage VDC	Release Voltage VDC	Coil Resistance : 10%	Nominal Voltage VAC	Pull-in Voltage VAC	Release Voltage VAC	Coil Resistance : 10%
5	4.0	0.50	30	6	4.80	1.80	12
6	4.8	0.60	40	12	9.60	3.60	42
12	9.6	1.20	160	24	19.2	7.20	168
24	19.2	2.40	640	48	38.4	14.4	675
48	38.4	4.80	2560	120	96.0	36.0	3500
110	88.0	11.0	12100	220/240	176.0	66.0	14000/16500




3604

Socket type



RT704B

Dimension.Bottom View



Reference Data

