



LTU3 70/35 (JXB-70EN)



LTU3 4/35S1 (JXB-4/35S1)

Outline dimension

Width/thickness/highness	(mm)	75/22/87
Bolt diameter	(mm)	M6
Toggle distance	(Nm)	0.5-1.0
Exhausted line length	(mm)	22

Rated data

Voltage/Current	(V)/(A)	800V/192A
Rated working frequency durable voltage	(A)	3.0KV
Cross-sectional area	(mm ²)	70mm ²

Clamp conductor range

Rigid conductor	(mm ²)	10-70
Flexible conductor	(mm ²)	10-70
Multi wire (with tubular bare reason)	(mm ²)	10-70

Installs rail

The belt general installs the foot, may install the guide rail (Steel system, Aluminum system)



End-cover board



Partition board



Inserts type joint

2 bit	
3 bit	
10 bit	

Fixed parts




Mark

Blank	
Crosswise prints	
Vertical prints	

Model	Color
TH35-7.5	Gray
LTU3-70G	Gray
LTW	Gray
EW/35	Gray
EW1/35	Gray
LZB 6	
LZB 6 (Horizontal)	White
LZB 6 (Vertical)	

Model	Color
TH35-7.5	Gray
LTU3-4/2-2G	Gray
LTW	Gray
LTU3-4/2-2/2L	
LTU3-4/2-3/2L	
LTU3-4/2-10/2L	
EW/35	Gray
EW1/35	Gray
LZB 6	
LZB 6 (Horizontal)	White
LZB 6 (Vertical)	



LTU3 W16/1 (JXB-W16/1)



LTU3 RD (JXB-RD)



LTU3 B (JXB-B)

Mark stand

65/8/48.5
M3.5
0.8-1.6
12

400V/41A
2.5KV
6mm ²

0.5-10
0.5-10
0.5-6

Model	Color
TH35-7.5	Gray
LTU3-6SG	Gray
LTW	灰色 Gray
LTU3-6S/2L	
LTU3-6S/3L	
LTU3-6S/10L	
EW/35	Gray
EW1/35	Gray
LZB 6	
LZB 6 (Horizontal)	White
LZB 6 (Vertical)	

58/6/48.5
M3
0.5-0.7
10

500V/6.3A
6.3KV
4mm ²

1.0-4
1.0-2.5

Model	Color
TH35-7.5	Gray
LTU3-2.5RDG	Gray
LTW	Gray
EW/35	Gray
EW1/35	Gray
LZB 6	
LZB 6 (Horizontal)	White
LZB 6 (Vertical)	

43/9.5/35.5

Model	Color
TH32-7.5	Gray
LZB 6	
LZB 6 (Horizontal)	White
LZB 6 (Vertical)	